

In situ permeability measurement with the BAT Permeameter

Quick Manual Outflow test



BAT Geosystems AB
Box 1060
186 26 Vallentuna
Tel +46851170600
Fax +46851173361

BAT Geosystems AB
Hällebergsvägen 5
443 60 Stenkullen
Tel +46317890600
Fax +46851173361

www.bat-gms.com
info@bat-gms.com

Ver 2011-02-14



Warranty details

BAT Geosystems AB (BAT) warrants all new BAT products against defects in materials and workmanship for a period of 12 months from the date of invoice. During the warranty period, we will repair or, at our option, replace at no charge a product that proves to be defective provided that it is returned, shipping cost prepaid, to BAT.

BAT's liability and obligations in connection with any defects in materials and workmanship are expressly limited to repair or replacement, and the sole and exclusive remedy in the event of such defects shall be repair or replacement. BAT's obligations under this warranty are conditional upon it receiving prompt written notice of claimed defects within the warranty period and it's obligations are expressly limited to repair or replacement.

This warranty does not apply to products or parts thereof which have been altered or repaired outside of the BAT factory, or products damaged by improper installation or application, or subjected to misuse, abuse neglect or accident.

BAT Geosystems AB will not be liable for any incidental or consequential damage or expense incurred by the user due to partial or incomplete inoperability of it's products for any reason whatsoever or due to inaccurate information generated by its products.

All warranty service will be completed as soon possible. If delays are unavoidable customers will be contacted immediately.

	Page
Pre test measures	1
Introduction BAT Permeameter	2
BAT Permeameter Equipment	3
Assembly of equipment - Layout	4
Assembly of equipment - Stepwise	5
Setup of outflow test	7
Starting the BAT Permeameter test	9
Finishing the test	10
Test sheet - Inflow test	11
Test sheet - Outflow test	12

1) **Installation of BAT MKIII Filter Tip**

Install a BAT MKIII Filter Tip at desired depth and location. Follow the instructions from the “Installation of the BAT MKIII Filter Tip”-guide.

2) **Measurement of pore pressure**

Measure the actual pore pressure. Follow the instructions given in the “BAT Pore Pressure Guide”.

Dissipation of disturbance effects

When the BAT Filter Tip is pushed into the soil, excess pore pressures will be generated due to disturbance effects. The time needed for dissipation of these disturbance effects varies with the type soil. In soft, plastic clays it may take several days until the original pore pressure is restored. On the contrary, in stiff clay, silt and fine sand the dissipation of the excess pressures goes much quicker. The process of dissipation of excess pore pressures can be logged by the BAT Sensor.

Make sure that the installation excess pore pressure has dissipated before starting a permeability test. If unsure, leave the sensor connected to the BAT Filter Tip for 10 minutes. If, during this period, the reading is stable (± 0.01 m H₂O) a permeability test can be performed.

3) **Checking BAT Sensor**

Make sure that the battery unit of the sensor contains a fresh, alkaline battery. If unsure, change the battery. Normal life time of a battery when constant logging (1 minute interval) is about 3-4 weeks.

Introduction BAT Permeameter

The BAT Permeameter can measure permeabilities, k , in the range from $1 \cdot 10^{-7}$ m/s and lower.

An example of typical k -values for different soil types:

Fine gravel:	$1 - 1 \cdot 10^{-2}$ m/s
Coarse sand:	$1 \cdot 10^{-1}$ m/s - $1 \cdot 10^{-3}$ m/s
Medium sand:	$1 \cdot 10^{-2}$ m/s - $1 \cdot 10^{-4}$ m/s
Fine sand:	$1 \cdot 10^{-3}$ m/s - $1 \cdot 10^{-5}$ m/s
Coarse silt:	$1 \cdot 10^{-4}$ m/s - $1 \cdot 10^{-6}$ m/s
Medium silt:	$1 \cdot 10^{-6}$ m/s - $1 \cdot 10^{-7}$ m/s
Fine silt:	$1 \cdot 10^{-7}$ m/s - $1 \cdot 10^{-8}$ m/s
Clay:	$< 1 \cdot 10^{-8}$ m/s

Typical time for stabilisation for different k -values, i.e. time of testing:

$k \approx 10^{-7}$ m/s ; $t_{stab} \approx 1$ minute
$k \approx 10^{-8}$ m/s ; $t_{stab} \approx 10$ minutes
$k \approx 10^{-9}$ m/s ; $t_{stab} \approx 1$ hour
$k \approx 10^{-10}$ m/s ; $t_{stab} \approx 10$ hours

Theory of the BAT Permeability Test

The BAT Permeability Test is a type of "falling head" test. The evaluation of the test is made by using Hvorslev's equation *).


Parameters:

F	= Hvorslev's flow factor	mm
	BAT MKIII Standard: 230 mm	
	BAT MKIII Vadose: 194 mm	
k	= coefficient of permeability	m/s
U_0	= equilibrium pore pressure in-situ (absolute)	m H ₂ O
P_0	= initial system pressure (absolute)	m H ₂ O
P_m	= system pressure at time t (absolute)	m H ₂ O
V_0	= initial system volume of air	ml
t	= time for the test	s

At any time t the corresponding coefficient of permeability k can be calculated using the following equation:


$$k = P_0 \cdot V_0 / (F \cdot t \cdot 10^3) \cdot \{ 1/U_0 \cdot P_0 - 1/U_0 \cdot P_m + 1/U_0^2 \cdot \ln[(P_0 - U_0)/P_0 \cdot P_m / (P_m - U_0)] \}$$

BAT Permeameter Equipment




Contents:

- | | |
|-----------------------------|-------------------------------|
| 1. Test container housing | 8. Syringes (25 ml & 10 ml) |
| 2. Test container (35 ml) | 9. Container for used needles |
| 3. Extension adapter | 10. Double ended needles |
| 4. Quick coupling sleeve | 11. Vacuum pump with |
| 5. Spare screws and springs | Manometer(see APPENDIX 1 |
| 6. Screwdriver for mounting | for use of the Vacuum Pump) |
| of double ended needle | 12. Blue needles |
| 7. Spare septas | 13. Cable Clamp |



PRECAUTIONS

- Handle all parts carefully, especially the glass containers.
- Use only sharp needles. In general do not re-use needles, especially in case the set is used for sampling.
- Store the set in a dry climate.
- Do not use any tools to assemble the set. Finger tight is enough.



Transfer nipple & extension adapter

- screw the transfer nipple until it seats in the sensor cavity. Firstly, make sure the parts all are dry.
- Attach a blue needle onto the transfer nipple.
- Mount the extension adapter onto the transfer nipple.

Test container


Outflow test - unsaturated soil conditions

- Open the test container in one end by removing the screw cap and the septum.
- Fill the test container with a selected volume of water, using a syringe. See **PAGE 7** for more details.
- Close the test container. Finger tight is enough!



Container housing assembly and connection of IS Field Unit

- Carefully insert the test container into the container housing.
- Screw the extension adapter onto the open end of the container housing.
- Connect the IS Field Unit, choose Display Mode (see page 7).
- The pressure in the test container can now be measured with the IS Field Unit (see also APPENDIX 1). After assembly hold the test unit horizontal or pointing downwards.



Unsaturated soil conditions & negative pore pressure situation

For unsaturated soil conditions the BAT Permeability test must be carried out as an outflow test. It is also assumed that a negative pore pressure situation is prevailing, i.e.: $U_0 \leq p_{\text{atm}}$. This condition is normally prevailing for *compacted clay liners*. For outflow tests in unsaturated conditions the BAT MKIII Vadose is needed.

The outflow test starts with a partly water-filled Test container.

Initial water volume $\Delta V_{\text{H}_2\text{O}}$

Porewater pressure interval $8 \leq U_0 \leq p_{\text{atm}}$

For the porewater pressure interval of $8 \leq U_0 \leq p_{\text{atm}}$: $\Delta V_{\text{H}_2\text{O}} = 10$ (ml)

Porewater pressure interval $1 \leq U_0 < 8$

The water volume, $\Delta V_{\text{H}_2\text{O}}$, for pressure interval $1 \leq U_0 < 8$ is calculated as follows:

$$\Delta V_{\text{H}_2\text{O}} \approx (35 - 3,1 \cdot U_0) \quad (\text{ml})$$

The volume $\Delta V_{\text{H}_2\text{O}}$ is injected without using the blue needle.

Initial system pressure P_0


Depending on the magnitude of the equilibrium pore pressure U_0 the following initial system pressures P_0 are recommended:

Equilibrium pore pressure interval (m H₂O): $9 < U_0 \leq p_{\text{atm}}$ $8 \leq U_0 \leq 9$ $1 \leq U_0 < 8$
 Recommended initial system pressure (m H₂O): $P_0 = 1,1 \cdot U_0$ $P_0 = 1,25 \cdot U_0$ $P_0 = p_{\text{atm}}$



All pressures are in absolute values.

With the sensor and field unit connected the system pressure P_0 is adjusted with a syringe and blue needle.

Continue to page 9!



P_0 = System pressure in test container
 U_m = sensor pressure (if BAT Permemeter not connected)
 U_0 = pore pressure = $U_m + 0.2\text{m H}_2\text{O}$ (pressure head compensation)



Starting the BAT Permeameter test



With the system pressure P_0 (and ΔV_{H_2O} for the outflow test) set correctly the next step is as follows:

Temperature equilibrium

With knowledge of the installation depth, use the cable clamp to fix the cable and let the BAT Permeameter rest above the filter tip before the test.

With the BAT/IS-Field Unit connected you can monitor the temperature equilibrium process. When the system pressure P_0 is stable note this value in the test sheet.

Starting the test

1) Prior to the start of the test, prepare the Field Unit by opening the "Start Measure" menu. Select both sensor and temperature logging (sensor+temp) and a suitable time interval. To start with it is recommended to use 1 min logging interval. At a later stage of the test the logging interval can be changed (increased) without any interference with the ongoing logging of test data.

2) Thereafter, place the marker on the **OK**-option at the bottom of the menu, without starting the logging.

3) The next step is to connect the test equipment to the BAT Filter Tip. Thus, remove the cable clamp and gently lower the equipment the remaining 0.2 – 0.3 m down to the Filter Tip. At the same moment the equipment connects to the Filter Tip, **press OK** on the Field Unit and the test is running. Open the "**Display**" menu of the Field Unit to have a visual check that the test is running, i.e. the pressure shall gradually change.

4) Depending on soil type the testing time may vary from 5 minutes up to 24 hours or more. After about one hour the measuring interval of the sensor can be increased to 10 minutes or more. This is simply done by activating the "Start measure" function of the BAT/IS-Field Unit and select a new logging interval.

5) The test can normally be evaluated at a pressure equalization of 50-80% ($P_{50} - P_{80}$). Before finishing the test take a reading of the atmospheric pressure and fill in the value in the Test Protocol.



Finishing the test

When P_{50} (or P_{80}) is reached the test can be terminated by following the steps below:

1) Note the value of P_{end} in the test sheet.

2) Gently pull the equipment from the installation and measure the volume water inside the test container. This is the V_{end} -value in the test sheet. The volume can be measured by pouring the liquid into a syringe sealed with a rubber septa to the needle. It can also be measured more accurately at the office at a later stage.

3) Note the atmospheric pressure at the end of the test. This might be of importance if dramatic weather (pressure) changes has occurred during the test.

Now the field part of the test is completed. Please refer to the "**In situ permeability measurement with the BAT Permeameter**"-manual for evaluation of the permeability.

If running more tests before downloading the data to a PC, just remember do not clear the data between the tests. Keep notes on the starting time and starting pressures of each test and each set of test data is easily separated when processing it on a PC.

TEST SHEET - OUTFLOW TEST

Site

Date/Time

Measuring point:

BAT Sensor no

Installation depth of filter tip

m

Test performed by

Type of filter tip

BAT MKIII Standard

BAT MKIII Vadose

Initial atmospheric pressure

mH₂O

time

Final atmospheric pressure

mH₂O

time

U₀, pore pressure at equilibrium

mH₂O

(U₀ = U_m + 0.2 mH₂O)

P₀, system pressure at start of test (at temperature equilibrium)

mH₂O

(displayed P_m value)

P₅₀, system pressure at 50% pressure recovery (calculated)

mH₂O

P₅₀ = P₀ - 0.5(P₀ - U₀)

P₈₀, system pressure at 80% pressure recovery (calculated)

mH₂O

P₈₀ = P₀ - 0.5(P₀ - U₀)

P_{end}, final system pressure (measured)

mH₂O

V_v, volume liquid in system at start of test

ml

V₀, volume of air in system at start of test (35-V_v)

ml

V_{calc}, calculated volume liquid in system at end of test

ml

V_{calc} = [P₀V_v - 35(P₀ - P_{end})]/P_{end}

V_{end}, measured volume liquid in system at end of test

ml

Coefficient of permeability, k =

*10-

m/s, calculated at

%

pressure equalisation

Notes: _____
